

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 April 2001 (26.04.2001)

PCT

(10) International Publication Number
WO 01/29832 A1

(51) International Patent Classification:
7/007, 20/12

G11B 7/00,

(74) Agent: RIEM, Charles, H.; Internationaal Octrooibureau
B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: PCT/EP00/10095

(22) International Filing Date: 12 October 2000 (12.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99203443.9 20 October 1999 (20.10.1999) EP
00200047.9 7 January 2000 (07.01.2000) EP

(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. (NL/NL); Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors: HEEMSKERK, Jacobus, P., J.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL); VAN WOUDEBERG, Roel; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GR, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: RECORD CARRIER OF A READ-ONLY TYPE AND READ DEVICE

WO 01/29832 A1



(57) Abstract: A record carrier of a read-only type has information in a track. The information is subdivided in addressable blocks and a number of blocks constitute an information unit. The information unit is the minimal unit for error correction according to a format for writable record carriers. On the read-only record carrier a linking area is provided between information units. This has the advantage that compatibility with recordable record carriers is improved.

Record carrier of a read-only type and read device.

The invention relates to a record carrier of a read-only type comprising information in a track.

The invention further relates to a method of manufacturing a record carrier of a read-only type in which method an information layer of the record carrier is provided with 5 marks constituting a track representing information.

The invention further relates to a read device for reading the record carrier.

Record carriers of a read-only type are well-known, e.g. the Compact Disc 10 (CD). Such read-only type record carriers are manufactured in a mass production process, e.g. for optical record carriers by stamping replicas from a master disc. Hence the information is applied to the record carrier in one step, and the track has a single, continuing pattern of marks representing said information. The information is logically subdivided in addressable blocks of data words and corresponding control words, e.g. addresses. An 15 addressable block is the amount of data words which is logically handled as one item of data, e.g. 2048 bytes. Hence the addressable blocks constitute logical amounts of user data which can be retrieved individually, e.g. computer data on a CD-ROM. On the other hand recordable-type record carriers are known, e.g. CD-R or CD-RW. Recordable-type record carriers are usually provided with information in a recording device by writing information 20 signals in a preformed track consecutively or random at selected locations. Such recording in different sessions in time may take place in one recording device or in different recorders. The recording in different sessions of information signals adjacently in the track is called linking. A method and apparatus for linking successively recorded information signals on a recordable record carrier is known from US 5,187,699. The minimal amount of information 25 which has to be recorded without interruption by such an information signal is inter alia determined by the error correction system. Such amount is called an information unit and comprises a number of the logically addressable blocks, at least one but usually 8 or 16, and Error Correcting Codes (ECC) covering said blocks. Information units are to be recorded at predefined locations indicated by position information in the pregroove. Hence in between

information units there may be a boundary between signals recorded at different instants, called a link position. In the known linking method, after a first information signal is completely recorded, the recording process is continued for a predetermined period after a last frame of the signal up to the link position. When a next information signal is to be recorded, the recording process is started at the link position by adding dummy information (usually zero data) up to the start of the following predefined location. Hence the area between the information units does not contain valid information, and is called a linking area, which linking area includes said link position. Usually the rules for the storage of information in the track on a record carrier are called a format, e.g., a format for recordable type record carriers. A problem is, that read devices for reading several record carrier types must first distinguish between the read-only type and the recordable type before the read signal can be decoded according to the correct format. Simple read devices which are equipped only to read the format of the record carriers of the read-only type may be disturbed when such a linking area is read, which results in errors in the output signals.

It is an object of the invention to provide a record carrier and read device which allow effective linking and obviate the above problems.

For this purpose, the read-only type record carrier as described in the opening paragraph has a track comprising the information subdivided in information units that are constituted by a predetermined number of addressable blocks, which track further comprises linking areas provided between the information units according to a format for recordable type record carriers. Further the device as described in the opening paragraph is provided with signal processing means for retrieving the information and discarding the linking area. The effect of the linking area in the read-only type record carrier is, that read devices need only be equipped for reading one format and can read the recordable discs without any disruption of the read process, because the linking area is part of the format. Further the compatibility between different types of record carriers is improved because the storage capacity of the read-only type record carrier is not larger than the capacity of the recordable type due to the presence of linking areas in both types, and because the relation between logical addresses of blocks and their physical locations can be the same in both types.

The invention is also based on the following recognition. Usually a lot of effort is required to provide linking for recordable type record carriers which are to be compatible to read-only type record carriers. Such a linking system may require a highly

accurate recording device to create only a small linking area which can be dealt with by the error correcting system provided in players for read-only record carriers. By providing the linking area already in the read-only type disc format the read device is less complicated because only one format needs to be decoded. Further the recording device does not require a high accuracy linking circuit, but may create a normal size linking area.

A preferred embodiment of the record carrier is characterized in that the information is encoded by a channel code to an encoded signal comprising frames and in that the linking area comprises two frames. This has the advantage, that the first frame of the linking area may be used in a recording system to facilitate a run-out area for the previous information unit, while the second frame facilitates a run-in area for the next information unit. Hence a minimal loss of capacity is accomplished.

In a further embodiment of the record carrier at least one linking area comprises auxiliary information. This has the advantage, that the auxiliary information is exclusively available for read-only record carriers, for example copy protection keys, and cannot be easily copied to a recordable type record carrier, because on standard recording devices the contents of the linking area cannot be influenced externally.

Further advantageous, preferred embodiments according to the invention are given in the further dependent claims.

These and other aspects of the invention will be apparent from and elucidated further with reference to the embodiments described by way of example in the following description and with reference to the accompanying drawings, in which

Fig. 1 shows a record carrier,

Fig. 2 shows a reading device,

Fig. 3 shows a number of linked information units, and

Fig. 4 shows a linking area.

Corresponding elements in different Figs. have identical reference numerals.

Fig. 1a shows a disc-shaped record carrier 11 having a track 19 and a central hole 10. The track 19 is arranged in accordance with a spiral pattern of turns constituting substantially parallel tracks on an information layer. The record carrier is optically readable, called an optical disc, and is of read-only type. The information is represented on the

information layer by optically detectable marks along the track, e.g. indentations manufactured by pressing. The track comprises position information, e.g. addresses, for indication of the location of data blocks. A number of blocks constitute an information unit, which unit is provided with error correcting codes and is the minimally required amount of data for an error correcting process in a read device.

Fig. 1b is a cross-section taken along the line b-b of the record carrier 11, in which a transparent substrate 15 is provided with a reflecting layer 16 and a protective layer 17. The track 14 may be implemented as an indentation or an elevation, and marks are provided along the longitudinal direction of the track representing the information.

The record carrier 11 carries information represented by marks, which result in a modulated signal when optically detected. The modulated signal is subdivided in frames. A frame is a predefined amount of data preceded by a synchronizing signal. Usually such frames also comprise error correction codes, e.g. parity words, which however are related to a number of data blocks, i.e. a large number of frames. An example of such a recording system is known from the DVD system, in which the frames carry 172 data words and 10 parity words, which example is used in the description below. The data is organized in blocks of 2 KB and in information units comprising 16 blocks, hence the size of such a unit is 32KB user data. The unit comprises a number of frames which contain Error Correction Codes (ECC) for correcting errors in the user information in the unit, and it contains 2 layers of error correction. The first layer of error correction (called C1) corrects small errors like random errors, and the second layer (called C2) corrects the large error such as burst errors. A recording device should be able to write and/or rewrite such a block independently. Therefore a block is preceded by a run-in area not containing user data, but a dedicated pattern for settling the read-out electronics (e.g. gain, frequency and phase of the PLL). Further the block usually is also provided with a run-out area to prevent an abrupt ending of the read signal, which might disturb the read electronics. So for recordable record carriers a linking area is available between the units. The size of the linking area may be equal to a data block or even an information unit. According to the invention the linking area is introduced in the read-only record carrier having the same or similar contents as the writable record carrier. Advantageously the read device does not have to detect which type of record carrier is to be read, as the format of data storage is equal. In an embodiment the linking area consists of 2 frames. There will always be some errors on a link position but errors when stopping the recording of a unit can be positioned in the first frame, while errors due to starting a recording can be positioned in the second frame. In a further embodiment the linking area is

subdivided in a run-out field following the previous data block, a gap and a run-in field preceding the next data block.

Fig. 2 shows a playback device for reading a record carrier 11, which record carrier is identical to the record carrier shown in Fig. 1. The device is provided with a drive unit 21 for rotating the record carrier 1, and a read head 22 for scanning the track 19 on the record carrier. The apparatus is provided with a positioning unit 25 for coarsely positioning the read head 22 on the track in the radial direction (perpendicular to the length direction of the track). The read head comprises an optical system of a known type for generating a radiation beam 24 guided through optical elements and focused to a radiation spot 23 on a track of the information layer of the record carrier. The radiation beam 24 is generated by a radiation source, e.g. a laser diode. The read head further comprises a focusing actuator for moving the focus of the radiation beam 24 along the optical axis of said beam and a tracking actuator for fine positioning of the spot 23 in a radial direction on the center of the track. The tracking actuator may comprise for example coils for radially moving an optical element or a piezo element for changing the angle of a reflecting element with respect to the optical axis of the beam 24. The radiation reflected by the information layer is detected by a detector of a usual type, e.g. a four-quadrant diode, in the read head 22 for generating a read signal and further detector signals including a tracking error and a focusing error signal, which are applied to said tracking and focusing actuators. The read signal is processed by a read means 27 to retrieve the data, which read means are of a usual type for example comprising a channel decoder. The retrieved data is passed to a data selector 28. The data selector selects the information units and skips the read signal from the linking areas in between the information units. The selected data is passed on to the error correction unit 29 which perform the error correction to generate an output signal 30. In a different embodiment there is no separate data selector, but the error correction unit is provided with a frame detector which detects the frames on the read signal, and discards the linking frames and combines the frames constituting an information unit. The device is further provided with a control unit 20 for receiving commands from a user or from a host computer for controlling the apparatus via control lines 26, e.g. a system bus, connected to the drive unit 21, the positioning unit 25, the read means 27 and the data selector 28, and possibly also the error correction unit 29. To this end, the control unit 20 comprises control circuitry, for example a microprocessor, a program memory and control gates, for performing the usual control procedures. The control unit 20 may also be implemented as a state machine in logic circuits.

Fig. 3 shows a number of linked information units. A part of a logical sequence 31 of information units is indicated. A first information unit 32 is named N-1, and followed by a linking area 33. Thereafter a next information unit 34 is named N, followed by a further linking area 35 and a third information unit 36 named N+1. Each pair of information units is separated by a linking area, and therefore in a recordable system a compatible record carrier can be recorded without difficulties. It must be noted that the sequence as shown in Fig. 3 is present on a read-only record carrier which does not require any linking areas. However, as the playback device is arranged to cope with the linking areas, any recorded record carrier can easily be read on the same device. In an embodiment the linking area has a length of two frames as described above with reference to Fig. 1.

Fig. 4 shows a linking area. A detail of the logical sequence 31 of information units is indicated. The preceding information unit 32 is named N-1, and followed by the linking area 33 and the next information unit 34 named N. The linking area 33 is subdivided in a run-out field 41 adjacent to the preceding unit 32, a gap 42, and a run-in field 43 immediately before the data area of the next unit N. The run-in field and the run-out field may be filled with a predetermined pattern of marks, usually short marks for synchronizing a read clock when reading. The gap 42 does not have a specific prescribed data content in the recordable type record carrier, because it remains unrecorded. When recording several information units consecutively the gap may also be recorded. In the read-only disc the gap may be an unrecorded area or may have some random data pattern. For recording the gap has the advantage, that the run-out field and the run-in field do not overlap and therefor are reliable and without unexpected errors. In a further embodiment the linking area in the read-only record carrier may be used to accommodate auxiliary data, e.g. access control data, a decryption key or a unique disc identification number. In particular the gap may advantageously be used to store copy control information, because on a recorder the content of the linking area cannot be influenced externally by the user and in particular the gap cannot be filled at all.

Although the invention has been explained by embodiments using the CD and DVD-optical recording format, it may be applied for any format for storage of units of information. For example the record carrier may also be a magnetic type disc or a tape. It is noted, that the invention may be implemented by means of both hardware and software, and that in this document the word 'comprising' does not exclude the presence of other elements or steps than those listed and the word 'a' or 'an' preceding an element does not exclude the presence of a plurality of such elements, that any reference signs do not limit the scope of the

claims, that "means" may be represented by a single item or a plurality and that several "means" may be represented by the same item of hardware. Further, the scope of the invention is not limited to the embodiments, and the invention lies in each and every novel feature or combination of features described above.

FIG. 3 is a block diagram of a system for recording and reproducing data. The system includes a recording device 30 and a reproducing device 32. The recording device 30 includes a recording head 30a and a recording medium 30b. The reproducing device 32 includes a reproducing head 32a and a reproducing medium 32b. The recording head 30a is connected to the recording medium 30b by a recording line 30c. The reproducing head 32a is connected to the reproducing medium 32b by a reproducing line 32c. The recording line 30c and the reproducing line 32c are connected to a control unit 34. The control unit 34 is connected to a data source 36 and a data sink 38. The data source 36 provides data to the recording head 30a, and the data sink 38 receives data from the reproducing head 32a. The control unit 34 controls the recording and reproducing operations of the system.

The recording device 30 and the reproducing device 32 are connected to the control unit 34 by a data bus 39. The data bus 39 is a bidirectional bus that allows data to be transferred between the recording device 30 and the reproducing device 32. The control unit 34 is a microprocessor that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

The recording head 30a is a recording head that records data on the recording medium 30b. The reproducing head 32a is a reproducing head that reproduces data from the reproducing medium 32b. The recording line 30c is a recording line that connects the recording head 30a to the recording medium 30b. The reproducing line 32c is a reproducing line that connects the reproducing head 32a to the reproducing medium 32b. The control unit 34 is a control unit that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

The data bus 39 is a data bus that connects the recording device 30 and the reproducing device 32 to the control unit 34. The data bus 39 is a bidirectional bus that allows data to be transferred between the recording device 30 and the reproducing device 32. The control unit 34 is a microprocessor that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

The recording head 30a is a recording head that records data on the recording medium 30b. The reproducing head 32a is a reproducing head that reproduces data from the reproducing medium 32b. The recording line 30c is a recording line that connects the recording head 30a to the recording medium 30b. The reproducing line 32c is a reproducing line that connects the reproducing head 32a to the reproducing medium 32b. The control unit 34 is a control unit that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

The data bus 39 is a data bus that connects the recording device 30 and the reproducing device 32 to the control unit 34. The data bus 39 is a bidirectional bus that allows data to be transferred between the recording device 30 and the reproducing device 32. The control unit 34 is a microprocessor that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

The recording head 30a is a recording head that records data on the recording medium 30b. The reproducing head 32a is a reproducing head that reproduces data from the reproducing medium 32b. The recording line 30c is a recording line that connects the recording head 30a to the recording medium 30b. The reproducing line 32c is a reproducing line that connects the reproducing head 32a to the reproducing medium 32b. The control unit 34 is a control unit that controls the recording and reproducing operations of the system. The data source 36 is a data source that provides data to the recording head 30a. The data sink 38 is a data sink that receives data from the reproducing head 32a.

CLAIMS:

1. Record carrier of a read-only type comprising information in a track, the information being subdivided in information units (32,34,36) that are constituted by a predetermined number of addressable blocks, which track further comprises linking areas (33,35) provided between the information units according to a format for recordable type record carriers.
5
2. Record carrier as claimed in claim 1, wherein the information is encoded to an encoded signal comprising frames and in that the linking area (33,35) comprises two frames.
- 10 3. Record carrier as claimed in claim 1, wherein the linking areas (33,35) comprise a run-out field (41), a gap (42) and a run-in field (43).
4. Record carrier as claimed in claim 1, wherein at least one linking area (33) comprises auxiliary information.
15
5. Method of manufacturing a record carrier of a read-only type in which method an information layer of the record carrier is provided with marks constituting a track representing information, wherein the information is subdivided in information units (32,34,36) that are constituted by a predetermined number of addressable blocks, and
20 wherein the track is provided with linking areas (33,35) between the information units according to a format for recordable type record carriers.
6. Read device for reading a record carrier of a read-only type comprising information in a track, the information being subdivided in information units (32,34,36) that
25 are constituted by a predetermined number of addressable blocks, which track further comprises linking areas (33,35) provided between the information units according to a format for recordable type record carriers, which device is provided with signal processing means (28) for retrieving the information and discarding the linking areas.

7. Read device as claimed in claim 6, wherein the signal processing means (28) comprise means for deriving auxiliary information from at least one linking area (33).

1/2




FIG. 1a

FIG. 1b




FIG. 2

2/2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

Inter. Application No

PCT/EP 00/10095

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B7/00 G11B7/007 G11B20/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 730 274 A (INCAT SYSTEMS SOFTWARE USA INC) 4 September 1996 (1996-09-04) claims 1-4,17; figure 4A column 22, line 6-10	1,2,4-7
X	EP 0 724 263 A (SONY CORP) 31 July 1996 (1996-07-31) claims 1,8,13; figures 1,2	1,5,6
A	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 09, 30 September 1997 (1997-09-30) & JP 09 115250 A (SONY CORP), 2 May 1997 (1997-05-02) abstract	1,5,6

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

2 February 2001

Date of mailing of the international search report

09/02/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Bernas, Y

10. 4. 2007 21.0.

PCT/EP 00/10095

1. *Chlorophyll a* and *Chlorophyll b* were determined by the method of Arar and Collins (1971).

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Application No

PCT/EP 00/10095

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0730274 A	04-09-1996	AU 707161 B	01-07-1999
		AU 4577396 A	05-09-1996
		CA 2169131 A	29-08-1996
		JP 8273334 A	18-10-1996
		US 6091686 A	18-07-2000
EP 0724263 A	31-07-1996	JP 8203210 A	09-08-1996
		AU 4214696 A	08-08-1996
		CN 1137675 A	11-12-1996
		SG 33669 A	18-10-1996
		US 5778257 A	07-07-1998
JP 09115250 A	02-05-1997	NONE	
JP 09171481 A	30-06-1997	NONE	
JP 11328864 A	30-11-1999	NONE	